



US009410932B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 9,410,932 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **METHOD OF MEASURING DISSOLVED METHANE IN SEAWATER**

G01N 30/88; G01N 21/61; G01N 7/14;
G01N 1/10; G01N 1/28; G01N 30/72; Y10T
436/214; B01D 61/36

(71) Applicant: **KOREA INSTITUTE OF
GEOSCIENCE AND MINERAL
RESOURCES**, Daejeon (KR)

See application file for complete search history.

(72) Inventors: **Ji-Hoon Kim**, Daejeon (KR); **Jiyoung
Choi**, Daejeon (KR); **Sungkyoung
Hong**, Daejeon (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2009/0084976 A1* 4/2009 Camilli H01J 49/24
250/397

(73) Assignee: **Korea Institute of Geoscience and
Mineral Resources**, Daejeon (KR)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 32 days.

Schluter et al., "Application of Membrane Inlet Mass Spectrometry
for Online and In Situ Analysis of Methane in Aquatic Environ-
ments", Journal of the American Society for Mass Spectrometry, vol.
19, Issue 10, Oct. 2008, pp. 1395-1402.*

(Continued)

(21) Appl. No.: **14/724,647**

(22) Filed: **May 28, 2015**

Primary Examiner — Jennifer Wecker

(65) **Prior Publication Data**

US 2015/0355155 A1 Dec. 10, 2015

(74) Attorney, Agent, or Firm — Alleman Hall McCoy
Russell & Tuttle LLP

(30) **Foreign Application Priority Data**

Jun. 9, 2014 (KR) 10-2014-0069154

(51) **Int. Cl.**

G01N 33/18 (2006.01)
G01N 30/04 (2006.01)
G01N 30/00 (2006.01)
G01N 30/72 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **G01N 33/1826** (2013.01); **B01D 61/36**
(2013.01); **G01N 1/10** (2013.01); **G01N 1/28**
(2013.01); **G01N 7/14** (2013.01); **G01N 21/61**
(2013.01); **G01N 30/00** (2013.01); **G01N 30/04**
(2013.01); **G01N 30/72** (2013.01); **G01N 30/88**
(2013.01); **Y10T 436/214** (2015.01)

(58) **Field of Classification Search**

CPC ... G01N 33/1826; G01N 30/00; G01N 30/04;

(57) **ABSTRACT**

Provided is a method of measuring dissolved methane in seawater, including: a) injecting a sample into a vacuum container containing a cadmium chloride solution injected thereto and refrigerating the vacuum container; b) shaking the vacuum container, and achieving temperature equilibrium with an ambient temperature; c) separating the dissolved methane from residue by passing the sample in the vacuum container through a methane separator; and d) analyzing the separated dissolved methane by a mass spectrometer. According to the method of measuring dissolved methane in seawater of the present invention, a recovery rate of dissolved methane may be maximally increased to improve an analysis rate accordingly, and an analysis of dissolved methane may be conducted even with a small amount of sample, and in addition to the measurement of the dissolved methane, a sulfur isotope analysis may be simultaneously conducted by using a sample from which the dissolved methane is extracted.

5 Claims, 2 Drawing Sheets

